

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **GASKET AND CARBON STRIPPER**

Article number: 84147

1.2 Relevant identified uses of the substance or mixture and uses advised against
FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Carbon deposit remover

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 1 H370 Causes damage to organs.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 1)

Hazard-determining components of labelling:

dichloromethane
Toluene
methanol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Labelling of packages where the contents do not exceed 125 ml**Hazard pictograms**

GHS02



GHS07



GHS08

Signal word Danger**Hazard-determining components of labelling:**

dichloromethane
Toluene
methanol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of the substances listed below with harmless additions.**Dangerous components:**

CAS: 75-09-2 EINECS: 200-838-9 Reg.nr.: 01-2119480404-41	dichloromethane ☠ Carc. 2, H351; ☠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335-H336	50-75%
CAS: 67-56-1 EINECS: 200-659-6 Reg.nr.: 01-2119433307-44	methanol ☠ Flam. Liq. 2, H225; ☠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ☠ STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	5-10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

		(Contd. of page 2)
CAS: 74-98-6 EINECS: 200-827-9	Propane liquefied ⚠ Flam. Gas 1A, H220	5-10%
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-10%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation In case of unconsciousness bring patient into stable side position for transport.
- After skin contact If skin irritation continues, consult a doctor.
- After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents
Carbon dioxide
Fire-extinguishing powder
Alcohol-resistant foam
Water haze
- For safety reasons unsuitable extinguishing agents Water jet.
- 5.2 Special hazards arising from the substance or mixture
Formation of toxic gases is possible during heating or in case of fire.
Formation of poisonous gases during heating or in fires.
- 5.3 Advice for firefighters
- Protective equipment:
Do not inhale explosion gases or combustion gases.
Wear full protective suit.
Put on breathing apparatus.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Keep away from ignition sources
Put on breathing apparatus.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Send for recovery or disposal in suitable containers.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Open and handle container with care.
- Information about protection against explosions and fires:
Protect against electrostatic charges.
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 3)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store container in a well ventilated position.

Storage class 2 B

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical systems: No further data; see item 7.

Components with limit values that require monitoring at the workplace:

75-09-2 dichloromethane

WEL Short-term value: 706 mg/m³, 200 ppm
Long-term value: 353 mg/m³, 100 ppm
BMGV, Sk

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm
Long-term value: 266 mg/m³, 200 ppm
Sk

108-88-3 Toluene

WEL Short-term value: 384 mg/m³, 100 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

Regulatory information WEL: EH40/2020

DNELs

75-09-2 dichloromethane

Dermal	Long term local effect	4750 mg/kg bw/dy (Worker)
Inhalative	Acute local effect	706 mg/m ³ (Worker)
	Long term local effect	353 mg/m ³ (Worker)

67-56-1 methanol

Dermal	Acute systemic effect	40 mg/kg bw/day (Worker)
	Long term systemic effect	40 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	260 mg/m ³ (Worker)
	Acute local effect	260 mg/m ³ (Worker)
	Long term local effect	260 mg/m ³ (Worker)
	Acute systemic effect	260 mg/m ³ (Worker)

108-88-3 Toluene

Dermal	Long term systemic effect	384 mg/kg bw/day (Worker)
Inhalative	Long term systemic effect	192 mg/m ³ (Worker)
	Acute local effect	384 mg/m ³ (Worker)
	Long term local effect	192 mg/m ³ (Worker)
	Acute systemic effect	384 mg/m ³ (Worker)

PNECs

75-09-2 dichloromethane

PNEC	0.54 mg/l (Aqua (freshwater))
	26 mg/l (Aqua (intermittent))
	0.194 mg/l (Aqua (marine water))
	0.972 mg/kg (Freshwater sediment)
	26 mg/l (Sewage treatment plant)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 4)

	0.583 mg/kg (Soil)
67-56-1 methanol	
PNEC	570.4 mg/kg (AMS) 154 mg/l (Aqua (freshwater)) 1540 mg/l (Aqua (intermittent)) 15.4 mg/l (Aqua (marine water)) 100 mg/l (Sewage treatment plant) 23.5 mg/kg (Soil)
108-88-3 Toluene	
PNEC	0.68 mg/l (Freshwater sediment) 0.68 mg/l (Marine water sediment) 13.61 mg/l (Sewage treatment plant) 2.89 mg/kg (Soil)
Ingredients with biological limit values:	
75-09-2 dichloromethane	
BMGV	30 ppm Medium: end-tidal breath Sampling time: post shift Parameter: carbon monoxide

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Take off immediately all contaminated clothing
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Breathing equipment:

Filter AX / P (EN 14387)
In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Protection of hands:



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Wear suitable gloves tested to EN 374

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level 6 > 480 minutes

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses (EN 166)

Tightly sealed safety glasses. (EN 166)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 5)

· **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Whitish
Odour:	Characteristic

· Change in condition

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not applicable, as aerosol

· **Flash point:** Not applicable, as aerosol· **Ignition temperature:** 455 °C· **Self-inflammability:** Product is not selfigniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· Critical values for explosion:

Lower:	1.2 Vol %
Upper:	44 Vol %

· **Vapour pressure at 20 °C:** 8300 hPa· **Density at 20 °C** 1.038 g/cm³

· Solubility in / Miscibility with

Water:	Partly miscible
--------	-----------------

· Solvent content:

Organic solvents:	1004g/l VOC
-------------------	-------------

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used and stored according to specifications.· **10.3 Possibility of hazardous reactions** No dangerous reactions known· **10.4 Conditions to avoid** No further relevant information available.· **10.5 Incompatible materials:** No further relevant information available.· **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

75-09-2 dichloromethane

Oral	LD50	2136 mg/kg (Rat)
------	------	------------------

67-56-1 methanol

Oral	LD50	13000 mg/kg (Rat)
	IC50	8000 (Algae)

74-98-6 Propane liquefied

	ErC 50	19.37 mg/l (Algae) (96 hr)
--	--------	----------------------------

108-88-3 Toluene

Oral	LD50	5000 mg/kg (Rat)
------	------	------------------

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 6)

Dermal	LD50	12124 mg/kg (Rabbit)
Inhalative	LC50 (4 hr)	49 mg/l (Mouse)
75-28-5 Isobutane		
	ErC 50	19.37 mg/l (Algae)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** Limited evidence of a carcinogenic effect.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure**
Causes damage to organs.
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

75-09-2 dichloromethane

EC50	2590 mg/l (Activated sludge) (40 mins)
LC50	4710 ug/l (Pimephales promelas) (8 days)
LC50 (48 hr)	27 mg/l (Daphnia magna)
LC50 (96 hr)	177-510 mg/l (Fish)
	193 mg/l (Pimephales promelas)
NOEC (28 days)	142 mg/l (Pimephales promelas)
NOEC	357 mg/l (Pimephales promelas) (8 days)

67-56-1 methanol

EC50 (48 hr)	24500 mg/l (Daphnia magna)
--------------	----------------------------

74-98-6 Propane liquefied

EC50 (48 hr)	69.43 mg/l (Daphnia magna)
LC50 (96 hr)	49.9 mg/l (Fish)

108-88-3 Toluene

EC50 (24 hr)	84 mg/l (Activated sludge)
EC50 (48 hr)	3.78 mg/l (Daphnia magna)
EC50 (72 hr)	10 mg/l (Algae)
LC50 (96 hr)	5.5 mg/l (Fish)
NOEC (7 days)	0.74 mg/l (Daphnia magna)

75-28-5 Isobutane

EC50 (48 hr)	69.43 mg/l (Daphnia magna)
LC50 (96 hr)	91.42 mg/l (Fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER




(Contd. of page 7)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG, IATA | AEROSOLS |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5TF Gases. |
| · Label | 2.1+6.1 |
| · IMDG | |
|  | |
| · Class | 2 Gases. |
| · Label | 2.1/6.1 |
| · IATA | |
|  | |
| · Class | 2 Gases. |
| · Label | 2.1 (6.1) |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No
No |
| · 14.6 Special precautions for user | |
| · Kemler Number: | Warning: Gases. |
| · EMS Number: | -
F-D,S-U |

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 8)

· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	120 ml
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	1
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1 (6.1)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
H3 STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE
P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
I	60.0
NK	13.0

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 78

Revision: 07.04.2021

Trade name: GASKET AND CARBON STRIPPER

(Contd. of page 9)

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing data specification sheet:** Environment protection department· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **Data compared to the previous version altered. ***